

ACT-410R Embedded Communication Manager



◆ Specifications

Model		ACT-410R	Others	
CPU			Operating System	Embedded Linux (gcc 4.3.2)
Default Configuration		ARM® Cortex®-A8 1GHz	RTC	Real Time Clock (Option)
Memory			Alarm	Buzzer
Default Configuration		1GB DDR3	Serial ID	License Management
Storage			Automatic Restart Trigger	Watchdog
NAND FLASH		1GB	Reset	Manual Reset Button
Expansion		1×SD Card Slots	Power	
Status Lamp			Input	5~28VDC (2 PIN terminal, anti-reverse protection)
Power		1×PWR	Typical Power Consumption	3.5W
Run		1×RUN(custom settings)	Environmental	
LAN		4×Link、ACT	Operating Temperature	-40~70℃
Serial Port		10×Serial Data	Storage Temperature	-40~85℃
Others		1×GPIO (custom settings)	Relative Humidity	20~90% (non-condensing)
Communication Interface			Mounting	Desktop, Rackmount
LAN		4×10/100M (RJ45), 1.5KV electromagnetic isolation	Dimensions (W×H×D)	483mm×44mm×261mm
Serial Port		10×RS-232/485 (terminal, RS-485 support ADDC), 2KV photoelectric isolation		
USB		2×USB 2.0 (internal)		

◆ Ordering Information

ACT-410R

Embedded Communication Manager, 4×10/100M LAN, 10×RS-232/485.



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008