

AE203M Rackmount IPC



◆ Specifications

Model		AE203M		
CPU			SATA	4×SATA 2.0
Default Configuration	Intel® Core™ i3 3.3GHz, 3M Cache, 64 Bit, Dual-Core	Ethernet	2×10/100/1000M	
Option	2nd & 3rd Intel® Core™ i3/i5/i7/Pentium® /Celeron® CPU series (LGA1155 Socket)	Audio	1×Line-in, 1×Line-out, 1×Mic	
Chipset		K&M Port	1×PS/2 Keyboard, 1×PS/2 Mouse	
Southbridge	Intel® H61	Display		
Memory		Video Port	1×VGA, 1×DVI-D	
Default Configuration	1×4GB DDR3 (2×DIMM, Support dual-channel)	Video Memory	On board, DVMT	
Max.	16GB	Option	Pluggable PCI-Ex16 graphics card	
Slots		Monitoring		
Mini PCI-E	1 (full-size)	Watchdog	0~255 Sec	
Storage		Power		
Default Configuration	1×2TB (With 24×7 operation)	Default Configuration	ATX 2U power	
Option	HDD(3.5"), SSD, mSATA	Others		
Driver		Keyboard & Mouse	Standard: USB Keyboard & 3D USB Mouse	
Default Configuration	DVD-ROM	Environmental		
Option	DVD-RW	Operating Temperature	0~55°C	
I/O Interface		Storage Temperature	-20~70°C	
Serial Port	Standard: 1×RS-232, 1×RS-232/422/485 (rear), 1×RS-232, 1×RS-232/422/485 (internal lead to external); 2×RS-232 (internal optional)	Relative Humidity	5~95% (non-condensing)	
Parallel Port	1 (internal optional)	Vibration	1.5g	
USB	Standard: 6×USB 2.0 (2 front, 4 rear), 2×USB 2.0 (internal optional)	Shock	10g	
		MTBF	50,000 hrs	
		Dimensions (W×H×D)	483mm×88mm×450mm	
		Chassis	Black panel, 3×8cm ball bearing fans,	
		Certification	42.5CFM FCC, CE	



Shanghai Nematron Technology Co., Ltd.
 189 Xinjun Ring Road, Suite C309 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China
 Email: marketing@nematron.com.cn