

AE406S-FL Rackmount IPC



◆ Specifications

Model		AE406S-FL
CPU		
Default Configuration	Intel® Core™ i3 3.3GHz, 3M Cache, 64 Bit, Dual-Core	
Option	2nd & 3rd Intel® Core™ i3/i5/i7/Pentium®/Celeron® CPU series (LGA1155 Socket)	
Chipset		
Southbridge	Intel® Q67	
Memory		
Default Configuration	2GB DDR3 (2×DIMM, Support dual-channel)	
Max.	16GB	
Slots		
PCI-Ex16	1	
PCI-Ex1	3	0
PCI-X	0	6
PCI	8	4
Mini PCIe	1 (full-size)	
PICMG	1×PICMG 1.3	
Storage		
Default Configuration	1×1TB (64M Cache, With 24×7 operation)	
Option	HDD (3.5"), SSD	
Driver		
Default Configuration	DVD-ROM	
Option	DVD-RW	
I/O Interface		
Serial Port	2 (1×RS-232, 1×RS-232 or RS-422/485, internal lead to external)	
Parallel Port	1 (internal optional)	
USB	Standard: 4×USB 2.0 (2 front, 2 rear); 4×USB 2.0 (internal optional)	

SATA	4×SATA 2.0, 2×SATA 3.0 (support RAID 0/1/5/10)
Ethernet	2×10/100/1000M (Intel® Network chip)
Audio	Option
K&M Port	USB
Display	
Video Port	1×VGA
Video Memory	On board, DVMT
Option	Pluggable PCI-Ex16 graphics card
Monitoring	
Watchdog	0~255 Sec
Power	
Default Configuration	ATX PS2 power
Option	Redundant power supply
Others	
Keyboard & Mouse	Standard: USB Keyboard & 3D USB Mouse
Environmental	
Operating Temperature	0~55℃
Storage Temperature	-20~70℃
Relative Humidity	5~95% (non-condensing)
Vibration	1.5g
Shock	10g
MTBF	50,000 hrs
Dimensions (W×H×D)	483mm×177mm×451mm
Chassis	Black panel, 2×9cm ball bearing fans, 51CFM, front fans can be removed without shutdown
Certification	FCC, CE



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008