

Fomax P170x Series Panel PC



◆ Specifications

Model	Fomax P1701	Fomax P1702	Fomax P1703
Basic Configuration			
CPU	Onboard 1st Intel® Core™ i5, 64 Bit, Dual-Core, BGA1288	Onboard 5th Intel® Core™ i5, 64 Bit, Dual-Core, BGA1168	Onboard Intel® Celeron® J1900 2.0GHz, up to 2.42GHz, 2M Cache, 64 Bit, Quad-Core
Memory	4GB DDR3 SODIMM (1× SODIMM), Max. 4GB	4GB DDR3L SODIMM (1× SODIMM), Max. 8GB	
Storage	1×500GB, With 24×7 operation (Standard) HDD (2.5"), SSD, mSATA (Option)		
Expansion Slots	1×Mini-PCIe (full-size)		
I/O Interface	4×RS-232/485, 2×RS-232 6×USB 2.0 (1 front, 4 rear, 1 Type-A internal) 1×SATA 2.0, 1×mSATA 2×10/100/1000M 1×VGA 1×Speaker-Out, 1×Mic-In 1×PS/2 Keyboard & Mouse (share with Y-Cable) Power Switch, Power Interface		
	On board, DVMT		
	Support		
Drivers			
Option	External USB DVD-ROM or DVD-RW		
Monitoring			
Watchdog	0~255 Sec		
Displays			
Type	17" SXGA TFT LCD		
Resolution	1280×1024		
Backlight	LED		
Touchscreen	5-wire resistive type (Standard)		
Power			
Power Input	12V~24VDC (3 Port terminal), with power adapter		
Mechanical Specifications			

Cooling	Fanless
Construction	Aluminum
Mounting	Panel, VESA (100mm)
Dimensions (W×H×D)	440mm×354mm×48.5mm
Cutout Size (W×H)	414mm×334mm
Environmental	
Operating Temperature	-20~60℃ (with wide temperature storage)
Storage Temperature	-40~80℃
Relative Humidity	5~95% (non-condensing)
IP Rating	IP65 compliant front panel



Shanghai Nematron Technology Co., Ltd.
 245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China
 Tel: +86 21 5109 6600 Fax: +86 21 5426 3008