

SE403P Rackmount Server



◆ Specifications

Model		SE403P
CPU		
Default Configuration	Intel® Xeon® 1.8GHz, 10M Cache, 64 Bit, Quad-Core	
Option	Intel® Xeon® E5-1600/E5-2600 CPU series (LGA2011 Socket)	
Chipset		
Southbridge	Intel® C602	
Memory		
Default Configuration	2GB REG ECC DDR3 (8×DIMM, Support dual channel)	
Max.	256GB	
Slots		
PCI-Ex16	2 (Auto switch to x8 link if adjacent PCI-Ex8 is occupied)	
PCI-Ex8	2 (w/ x8 Link), 1 (w/ x4 Link)	
PCI	1	
MIO	1 (only for Audio)	
Storage		
Default Configuration	1×1TB (64M Cache, With 24×7 operation)	
Option	HDD(3.5"), SSD	
Driver		
Default Configuration	DVD-ROM	
Option	DVD-RW	
I/O Interface		
Serial Port	1×RS-232 (rear), 1×RS-232 (internal lead to external)	
USB	Standard: 5×USB 2.0 (2 front, 2 rear, 1 Internal Type-A), 2×USB 3.0 (rear); 2×USB 2.0 (internal lead to external)	
SATA	4×SATA 2.0, 2×SATA 3.0 (support	

Ethernet		RAID0/1/5/10)
Audio		2×10/100/1000M (Intel® Network Chip)+1×Management port
K&M Port		Option 1×PS/2 Keyboard & Mouse (share with Y-Cable)
Display		
Video Port	1×VGA	
Video Memory	16MB	
Monitoring		
Watchdog	0~255 Sec	
Power		
Default Configuration	ATX PS2 power	
Option	Redundant power supply	
Others		
Keyboard & Mouse	Standard: PS/2 Keyboard & 3D USB Mouse	
Environmental		
Operating Temperature	0~50℃	
Storage Temperature	-20~70℃	
Relative Humidity	5~95% (non-condensing)	
Vibration	1.5g	
Shock	10g	
MTBF	50,000 hrs	
Dimensions (W×H×D)	483mm×177mm×510mm	
Chassis	Black panel, 2×12cm ball bearing fans, 93CFM	
Certification	FCC, CE	



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008