

Smart T6206 Emedded IPC



◆ Specifications

Model Smart T6206	
CPU	
Default Configuration	Intel® Core™ i3 3.1GHz, 3M Cache, 64 Bit, Dual-Core
Option	4th Intel® Core™ i3/i5/i7/Pentium®/Celeron® Processor (LGA1150 Socket)
Chipset	
Southbridge	Intel® H81
Memory	
Default Configuration	2GB DDR3 SODIMM (2× DDR3/DDR3L SODIMM), Max. 16GB
Slots	
PCI or PCIe	2× PCI or 1× PCI, 1× PCI-Ex16
Mini-PCIe	1× half-size
Storage	
Default Configuration	1× 500GB (With 24×7 operation)
Option	HDD (2.5"), SSD, mSATA
I/O Interface	
Serial Port	2× RS-232/422/485 (COM1-2), 3× RS-232 (COM3-5: front)
USB	Standard: 2× USB 2.0, 2× USB 3.0 (front); Option: 2× USB 2.0 (front)
SATA	1× SATA 3.0, 1× mSATA (Option)
LAN	2× 10/100/1000M (Intel® Network chip,

K&M Port	front) 1× PS/2 Keyboard & Mouse (share with Y-Cable)
Display	
Video Port	1× VGA
Video Memory	On board, DVMT
Monitoring	
Watchdog	0~255 Sec
Power	
Default Configuration	DC-in: 9~36VDC
Option	120 / 150W power adapter
Mechanical Specifications	
Cooling	Fanless
Construction	Aluminum & Steel
Mounting	Desktop, Wallmount
Dimensions (W×H×D)	236mm×126mm×225mm
Environmental	
Operating Temperature	-10~60℃
Storage Temperature	-20~80℃
Relative Humidity	5~95% (non-condensing)
Certification	FCC, CE



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008