

## VE415MP Rackmount IPC



### ◆ Specifications

Model	VE415MP		
CPU			
Default Configuration	Intel® Pentium® Dual-Core™ 3.3GHz, 3M Cache, 64 Bit, Dual-Core		optional, 1 TYPE-A) 4×SATA 3.0
Option	6th and 7th Intel® Core™ i3/i5/i7/Pentium®/Celeron® CPU series (LGA1151 Socket)		2×10/100/1000M (Intel® Network chip) 1×Line-in, 1×Line-out, 1×Mic
Chipset			
Southbridge	Intel® H110		
Memory			
Default Configuration	1×4GB DDR4 (4×DIMM, Support dual-channel)		1×VGA, 1×HDMI
Max.	32GB		On board, DVMT
Slots			
PCI-Ex16	1		Pluggable PCI-Ex16 graphics card
PCI-Ex4	1		
PCI-Ex1	1		
PCI	4		
Storage			
Default Configuration	1×1TB (With 24×7 operation)		Monitoring
Option	HDD (3.5"), SSD, mSATA		Watchdog
Driver			
Default Configuration	DVD-ROM		Power
Option	DVD-RW		Default Configuration
I/O Interface			
Serial Port	Standard: 2×RS-232/422/485 (rear), 2×RS-232 (internal lead to external); 2×RS-232 (internal optional)		ATX PS2 power
Parallel Port	1 (internal optional)		
USB	Standard: 4×USB 2.0 (2 front, 2 rear), 4×USB 3.0 (rear); 2×USB 2.0 (1 internal)		
SATA			SATA
Ethernet			Ethernet
Audio			Audio
K&M Port			K&M Port
Display			
Video Port	1×VGA, 1×HDMI		
Video Memory			
Option	On board, DVMT		
Monitoring			
Watchdog	0~255 Sec		
Power			
Default Configuration	ATX PS2 power		
Others			
Keyboard & Mouse	Standard: USB Keyboard & 3D USB Mouse		
Environmental			
Operating Temperature	0~50°C		
Storage Temperature	-20~70°C		
Relative Humidity	10~90% (non-condensing)		
Vibration	1.5g		
Shock	10g		
MTBF	50,000 hrs		
Dimensions (W×H×D)	483mm×177mm×450mm		
Chassis	1×12cm front fan, 2×8cm rear fans		
Certification	FCC, CE		



**Shanghai Nematron Technology Co., Ltd.**  
 189 Xinjun Ring Road, Suite C309 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China  
 Email: marketing@nematron.com.cn