

Smart T6009 Emedded IPC



◆ Specifications

Model	Smart T6009
CPU	
Default Configuration	Intel® Core™ i3 3.1GHz, 6M Cache, 64 Bit, Quad-Core 8th Intel® Core™ i3/i5/i7/Pentium®/Celeron® Processor (LGA1151 Socket, 35W)
Chipset	
Southbridge	Intel® H310
Memory	
Default Configuration	4GB DDR4 SODIMM (2× SODIMM), Max. 32GB
Slots	
Mini-PCle	1×E-key M.2, support CNVi
Storage	
Default Configuration	1×500GB (With 24×7 operation)
Option	HDD (2.5"), SSD, M.2
I/O Interface	
Serial Port	4×RS-232
USB	4×USB 3.0
SATA	1×SATA 3.0, 1×M-Key M.2
LAN	2×10/100/1000M
GPIO	8-Bit
Audio	1×Line-Out, 1×Mic

K&M Port	USB
Display	
Video Port	1×VGA, 1×HDMI (Standard); 1×eDP (Option)
Video Memory	On board, DVMT
Monitoring	
Watchdog	0~255 Sec
Power	
Default Configuration	9~24VDC, with 90~240VAC, 19VDC/6.32A/120W power adapter
Mechanical Specifications	
Cooling	Fanless
Construction	Aluminum & Steel
Mounting	Desktop, Wallmount
Dimensions (W×H×D)	264mm×58mm×199.4mm
Environmental	
Operating Temperature	-10~50°C
Storage Temperature	-20~60°C
Relative Humidity	10~90% (non-condensing)
Certification	CE, FCC



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008